



AREAS OF APPLICATION

- Entrance Lighting and Building Facades
- Parking Lots and outdoor areas
- Restaurant and Malls

PRODUCT BENEFITS

- Die-cast aluminum housing and Opal Polycarbonate diffuser
- Good Visual comfort, High colour rendering and light output
- Good glare reduction, Low maintenance and operation costs
- Suitable for use in indoor and Outdoor
- Protection grade: up to IP65 and meet the work requirements of external environment

PRODUCT FEATURES

- Protection: IP65 and IK06
- 3 Years Warranty.
- RAL9023 Pearl dark grey or customized

TECHNICAL DATA

Electrical data

Rated power	16W
Operating voltage	AC100-240V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	1040lm
Color rendering index Ra	80

Light Technical Data

Beam angle	45°
------------	-----

Dimensions

Inner Diameter	Ø155mm
Height	250

Temperature & operating conditions

Ambient Temperature	-20~+60C°
---------------------	-----------

General information

Mounting type	Surface
LED type	LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX 6156B-9	65 lm/W	16W	66	NO

TECHNICAL DRAWING

