



AREAS OF APPLICATION

-  Outdoor garden areas
-  Outdoor pathway

PRODUCT BENEFITS

-  Highly Efficient OSRAM LED Chip and high IP rating on luminaire front side
-  Slim and robust housing - constructed from durable die cast aluminium
-  Ruggedly constructed in-ground fixture for outdoor applications. Cutting dia. Ø200mm
-  Suitable for recessed mounting in any horizontal surface. Gravel must be used to ensure efficient drainage, 150 mm in deep and around.

PRODUCT FEATURES

-  IP 65 protection, Material: SS304 + Aluminum + Tempered Glass
-  RAL7039 (Quartz Grey Finish)
-  Using high-quality and high-precision material and structural waterproof, easy to maintain

TECHNICAL DATA

Electrical data

Rated power	20W
Operating voltage	AC 220-240V
Operating frequency	50-60Hz
Power factor	0.90

Photometrical data

Color temperature	2200K
Luminous flux(lm)	2200lm
Color rendering index Ra	80

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Diameter (mm)	Ø210mm
Height (mm)	150mm

temperature & operating conditions

Ambient Temperature	-15°C~+50°C
---------------------	-------------

General information

Mounting type	Recessed
LED type	OSRAM LED
Lifespan	30,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX-HLCTDM210	110lm/W	20W	65	NO

● TECHNICAL DRAWING

