













AREAS OF APPLICATION

-  Walls
-  Stairways
-  Steps

PRODUCT BENEFITS

-  Highly efficient OSRAM LED Chip and high rating on luminaire front side
-  Acrylic Frosted glass provides even illumination
-  Magnetized design for easy installation and maintenance
-  Low profile, flush to wall aesthetics with no visible hardware Can be mounted vertically or horizontally

PRODUCT FEATURES

-  IP66 protection
-  High quality OSRAM LED Chip.
-  Material: Die Cast Aluminum + Frosted Acrylic Diffuser, Finish:RAL7039 (Quartz Grey)

TECHNICAL DATA

Electrical data

Rated power	5W
Operating voltage	AC220-240V
Operating frequency	50-60Hz
Power factor	0.90

Photometrical data

Color temperature	2200K
Luminous flux(lm)	450lm
Color rendering index Ra	80

Light Technical Data

Beam angle	150°
------------	------

Dimensions

Width (mm)	212mm
Height (mm)	65mm

temperature & operating conditions

Ambient Temperature	-25°C~+50°C
---------------------	-------------

General information

Mounting type	Recessed
LED type	OSRAM Led
Lifespan	25,000h

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX-STP210	90lm/W	5W	66	NO

● TECHNICAL DRAWING

