













AREAS OF APPLICATION

-  Facade Lighting
-  Ambient Outdoor wall lighting
-  Buildings

PRODUCT BENEFITS

-  Highly efficient LED chip and high IP rating on luminaire front side provide a radial light effect
-  Slim and robust housing - constructed from durable die cast aluminium with radial effect optics
-  Ruggedly constructed surface mount fixture for outdoor applications
-  Guarantee a high level of weather and UV ray resistance.

PRODUCT FEATURES

-  IP67 protection
-  High quality LED Chip.
-  Material: Aluminium body + Acrylic

TECHNICAL DATA

Electrical data

Rated power	8W
Operating voltage	AC220-240V
Operating frequency	50~60Hz
Power factor	0.90

Photometrical data

Color temperature	2700K
Luminous flux(lm)	800lm
Color rendering index Ra	>80

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Diameter (mm)	Ø150mm
Height (mm)	50mm

temperature & operating conditions

Ambient Temperature	-30°C~+50°C
---------------------	-------------

General information

Mounting type	Surface
LED type	Bridgelux LED
Lifespan	25,000h

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX-WL08-WW	100lm/W	8W	67	NO

● TECHNICAL DRAWING

